



**BLIND FLANGE**

Nominal size		Outside diam. of flange	Thick. of flange	Diam. of raised face	No. of holes	Diam. of holes	Diam. of bolts	Diam. of bolt circle	Approx. weight pounds Kg
		O	C	R					
1/2"	<i>in.</i>	3.5	0.44	1.38	4	0.62	1/2	2.38	1
	<i>mm.</i>	88.9	11.2	35.1		15.7	12.7	60.5	0.5
3/4"	<i>in.</i>	3.88	0.5	1.69	4	0.62	1/2	2.75	2
	<i>mm.</i>	98.6	12.7	42.9		15.7	12.7	69.9	1
1"	<i>in.</i>	4.25	0.56	2	4	0.62	1/2	3.12	2
	<i>mm.</i>	108	14.2	50.8		15.7	12.7	79.2	1
1 1/4"	<i>in.</i>	4.62	0.62	2.5	4	0.62	1/2	3.5	3
	<i>mm.</i>	117.3	15.7	63.5		15.7	12.7	88.9	1
1 1/2"	<i>in.</i>	5	0.69	2.88	4	0.62	1/2	3.88	4
	<i>mm.</i>	127	17.5	73.2		15.7	12.7	98.6	2
2"	<i>in.</i>	6	0.75	3.62	4	0.75	5/8	4.75	5
	<i>mm.</i>	152.4	19.1	91.9		19.1	15.9	120.7	2
2 1/2"	<i>in.</i>	7	0.88	4.12	4	0.75	5/8	5.5	7
	<i>mm.</i>	177.8	22.4	104.6		19.1	15.9	139.7	3
3"	<i>in.</i>	7.5	0.94	5	4	0.75	5/8	6	9
	<i>mm.</i>	190.5	23.9	127		19.1	15.9	152.4	4
3 1/2"	<i>in.</i>	8.5	0.94	5.5	8	0.75	5/8	7	13
	<i>mm.</i>	215.9	23.9	139.7		19.1	15.9	177.8	6
4"	<i>in.</i>	9	0.94	6.19	8	0.75	5/8	7.5	17
	<i>mm.</i>	228.6	23.9	157.2		19.1	15.9	190.5	8
5"	<i>in.</i>	10	0.94	7.31	8	0.88	3/4	8.5	20
	<i>mm.</i>	254	23.9	185.7		22.4	19.1	215.9	9
6"	<i>in.</i>	11	1	8.5	8	0.88	3/4	9.5	26
	<i>mm.</i>	279.4	25.4	215.9		22.4	19.1	241.3	12
8"	<i>in.</i>	13.5	1.12	10.62	8	0.88	3/4	11.75	45
	<i>mm.</i>	342.9	28.4	269.7		22.4	19.1	298.5	20
10"	<i>in.</i>	16	1.19	12.75	12	1	7/8	14.25	70
	<i>mm.</i>	406.4	30.2	323.9		25.4	22.2	362	32
12"	<i>in.</i>	19	1.25	15	12	1	7/8	17	110
	<i>mm.</i>	482.6	31.8	381		25.4	22.2	431.8	50
14"	<i>in.</i>	21	1.38	16.25	12	1.12	1	18.75	140
	<i>mm.</i>	533.4	35.1	412.8		28.4	25.4	476.3	64
16"	<i>in.</i>	23.5	1.44	18.5	16	1.12	1	21.25	180
	<i>mm.</i>	596.9	36.6	469.9		28.4	25.4	539.8	82
18"	<i>in.</i>	25	1.56	21	16	1.25	1 1/8	22.75	220
	<i>mm.</i>	635	39.6	533.4		31.8	28.6	577.9	100
20"	<i>in.</i>	27.5	1.69	23	20	1.25	1 1/8	25	285
	<i>mm.</i>	698.5	42.9	584.2		31.8	28.6	635	129
24"	<i>in.</i>	32	1.88	27.25	20	1.38	1 1/4	29.5	430
	<i>mm.</i>	812.8	47.8	692.2		35.1	31.8	749.3	195