



**BLIND FLANGE**

Nominal size		Outside diam. of flange	Thick. of flange	Diam. of raised face	No. of holes	Diam. of holes	Diam. of bolts	Diam. of bolt circle	Approx. weight pounds Kg
		O	C	R					
1/2"	<i>in.</i>	5.25	1.19	1.38	4	0.88	3/4	3.5	7
	<i>mm.</i>	133.4	30.2	35.1		22.4	19.1	88.9	3
3/4"	<i>in.</i>	5.5	1.25	1.69	4	0.88	3/4	3.75	8
	<i>mm.</i>	139.7	31.8	42.9		22.4	19.1	95.3	4
1"	<i>in.</i>	6.25	1.38	2	4	1	7/8	4.25	11
	<i>mm.</i>	158.8	35.1	50.8		25.4	22.2	108	5
1 1/4"	<i>in.</i>	7.25	1.5	2.5	4	1.12	1	5.12	17
	<i>mm.</i>	184.2	38.1	63.5		28.4	25.4	130	8
1 1/2"	<i>in.</i>	8	1.75	2.88	4	1.25	1 1/8	5.75	23
	<i>mm.</i>	203.2	44.5	73.2		31.8	28.6	146.1	10
2"	<i>in.</i>	9.25	2	3.62	8	1.12	1	6.75	39
	<i>mm.</i>	235	50.8	91.9		28.4	25.4	171.5	18
2 1/2"	<i>in.</i>	10.5	2.25	4.12	8	1.25	1 1/8	7.75	56
	<i>mm.</i>	266.7	57.2	104.6		31.8	28.6	196.9	25
3"	<i>in.</i>	12	2.62	5	8	1.38	1 1/4	9	86
	<i>mm.</i>	304.8	66.5	127		35.1	31.8	228.6	39
4"	<i>in.</i>	14	3	6.19	8	1.62	1 1/2	10.75	135
	<i>mm.</i>	355.6	76.2	157.2		41.1	38.1	273.1	61
5"	<i>in.</i>	16.5	3.62	7.31	8	1.88	1 3/4	12.75	225
	<i>mm.</i>	419.1	91.9	185.7		47.8	44.5	323.9	102
6"	<i>in.</i>	19	4.25	8.5	8	2.12	2	14.5	345
	<i>mm.</i>	482.6	108	215.9		53.8	50.8	368.3	156
8"	<i>in.</i>	21.75	5	10.62	12	2.12	2	17.25	530
	<i>mm.</i>	552.5	127	269.7		53.8	50.8	438.2	240
10"	<i>in.</i>	26.5	6.5	12.75	12	2.62	2 1/2	21.25	1025
	<i>mm.</i>	673.1	165.1	323.9		66.5	63.5	539.8	465
12"	<i>in.</i>	30	7.25	15	12	2.88	2 3/4	24.38	1300
	<i>mm.</i>	762	184.2	381		73.2	69.9	619.3	590