



BLIND FLANGE

Nominal size		Outside diam. of flange	Thick. of flange	Diam. of raised face	No. of holes	Diam. of holes	Diam. of bolts	Diam. of bolt circle	Approx. weight pounds Kg
		O	C	R					
1/2"	<i>in.</i>	3.75	0.56	1.38	4	0.62	1/2	2.62	2
	<i>mm.</i>	95.3	14.2	35.1		15.7	12.7	66.5	1
3/4"	<i>in.</i>	4.62	0.62	1.69	4	0.75	1/2	3.25	3
	<i>mm.</i>	117.3	15.7	42.9		19.1	15.9	82.6	1
1"	<i>in.</i>	4.88	0.69	2	4	0.75	1/2	3.5	3
	<i>mm.</i>	124	17.5	50.8		19.1	15.9	88.9	1
1 1/4"	<i>in.</i>	5.25	0.75	2.5	4	0.75	1/2	3.88	4
	<i>mm.</i>	133.4	19.1	63.5		19.1	15.9	98.6	2
1 1/2"	<i>in.</i>	6.12	0.81	2.88	4	0.88	1/2	4.5	6
	<i>mm.</i>	155.4	20.6	73.2		22.4	19.1	114.3	3
2"	<i>in.</i>	6.5	0.88	3.62	8	0.75	5/8	5	8
	<i>mm.</i>	165.1	22.4	91.9		19.1	15.9	127	4
2 1/2"	<i>in.</i>	7.5	1		8	0.88	5/8	5.88	12
	<i>mm.</i>	190.5	25.4	104.6		22.4	19.1	149.4	5
3"	<i>in.</i>	8.25	1.12	5	8	0.88	5/8	6.62	16
	<i>mm.</i>	209.6	28.4	127		22.4	19.1	168.1	7
3 1/2"	<i>in.</i>	9	1.19	5.5	8	0.88	5/8	7.25	21
	<i>mm.</i>	228.6	30.2	139.7		22.4	19.1	184.2	10
4"	<i>in.</i>	10	1.25	6.19	8	0.88	5/8	7.88	27
	<i>mm.</i>	254	31.8	157.2		22.4	19.1	200.2	12
5"	<i>in.</i>	11	1.38	7.31	8	0.88	4-Mar	9.25	35
	<i>mm.</i>	279.4	35.1	185.7		22.4	19.1	235	16
6"	<i>in.</i>	12.5	1.44	8.5	12	0.88	3/4	10.62	50
	<i>mm.</i>	317.5	36.6	215.9		22.4	19.1	269.7	23
8"	<i>in.</i>	15	1.62	10.62	12	1	3/4	13	81
	<i>mm.</i>	381	41.1	269.7		25.4	22.2	330.2	37
10"	<i>in.</i>	17.5	1.88	12.75	16	1.12	1	15.25	124
	<i>mm.</i>	444.5	47.8	323.9		28.4	25.4	387.4	56
12"	<i>in.</i>	20.5	2	15	16	1.25	1 1/8	17.75	185
	<i>mm.</i>	520.7	50.8	381		31.8	28.6	450.9	84
14"	<i>in.</i>	23	2.12	16.25	20	1.25	1 1/8	20.25	250
	<i>mm.</i>	584.2	53.8	412.8		31.8	28.6	514.4	113
16"	<i>in.</i>	25.5	2.25	18.5	20	1.38	1 1/4	22.5	295
	<i>mm.</i>	647.7	57.2	469.9		35.1	31.8	571.5	134
18"	<i>in.</i>	28	2.38	21	24	1.38	1 1/4	24.75	395
	<i>mm.</i>	711.2	60.5	533.4		35.1	31.8	628.7	179
20"	<i>in.</i>	30.5	2.5	23	24	1.38	1 1/4	27	505
	<i>mm.</i>	774.7	63.5	584.2		35.1	31.8	685.8	229
24"	<i>in.</i>	36	2.75	27.25	24	1.62	1 1/2	32	790
	<i>mm.</i>	914.4	69.9	692.2		41.1	38.1	812.8	358