



BLIND FLANGE

Nominal size		Outside diam. of flange	Thick. of flange	Diam. of raised face	No. of holes	Diam. of holes	Diam. of bolts	Diam. of bolt circle	Approx. weight pounds Kg
		O	C	R					
1/2"	in.								
	mm.								
3/4"	in.								
	mm.								
1"	in.								
	mm.								
1 1/4"	in.								
	mm.								
1 1/2"	in.								
	mm.								
2"	in.								
	mm.								
2 1/2"	in.								
	mm.								
3"	in.								
	mm.								
3 1/2"	in.								
	mm.								
<p>Sizes 1/2" thru 3 1/2" are identical with class 600</p>									
4"	in.	10	1.38	6.19	8	1	39637	7.88	33
	mm.	254	35.1	157.2		25.4	22.2	200.2	15
5"	in.	11	1.5	7.31	8	1	39637	9.25	44
	mm.	279.4	38.1	185.7		25.4	22.2	235	20
6"	in.	12.5	1.62	8.5	12	1	39637	10.62	61
	mm.	317.5	41.1	215.9		25.4	22.2	269.7	28
8"	in.	15	1.88	10.62	12	1.12	1	13	100
	mm.	381	47.8	269.7		28.4	25.4	330.2	45
10"	in.	17.5	2.12	12.75	16	1.25	1 1/8	15.25	155
	mm.	444.5	53.8	323.9		31.8	28.6	387.4	70
12"	in.	20.5	2.25	15	16	1.38	1 1/4	17.75	225
	mm.	520.7	57.2	381		35.1	31.8	450.9	102
14"	in.	23	2.38	16.25	20	1.38	1 1/4	20.25	290
	mm.	584.2	60.5	412.8		35.1	31.8	514.4	132
16"	in.	25.5	2.5	18.5	20	1.5	1 3/8	22.5	370
	mm.	647.7	63.5	469.9		38.1	34.9	571.5	168
18"	in.	28	2.62	21	24	1.5	1 3/8	24.75	455
	mm.	711.2	66.5	533.4		38.1	34.9	628.7	206
20"	in.	30.5	2.75	23	24	1.62	1 1/2	27	587
	mm.	774.7	69.9	584.2		41.1	38.1	685.8	266
24"	in.	36	3	27.25	24	1.88	1 3/4	32	890
	mm.	914.4	76.2	692.2		47.8	44.5	812.8	404