



### BLIND FLANGE

Nominal size		Outside diam. of flange	Thick. of flange	Diam. of raised face	No. of holes	Diam. of holes	Diam. of bolts	Diam. of bolt circle	Approx. weight pounds Kg
		O	C	R					
1/2"	in.	3.75	0.56	1.38	4	0.62	1/2	2.62	2
	mm.	95.3	14.2	35.1		15.7	12.7	66.5	1
3/4"	in.	4.62	0.62	1.69	4	0.75	5/8	3.25	3
	mm.	117.3	15.7	42.9		19.1	15.9	82.6	1
1"	in.	4.88	0.69	2	4	0.75	5/8	3.5	4
	mm.	124	17.5	50.8		19.1	15.9	88.9	2
1 1/4"	in.	5.25	0.81	2.5	4	0.75	5/8	3.88	5
	mm.	133.4	20.6	63.5		19.1	15.9	98.6	2
1 1/2"	in.	6.12	0.88	2.88	4	0.88	3/4	4.5	8
	mm.	155.4	22.4	73.2		22.4	19.1	114.3	4
2"	in.	6.5	1	3.62	8	0.75	5/8	5	10
	mm.	165.1	25.4	91.9		19.1	15.9	127	5
2 1/2"	in.	7.5	1.12	4.12	8	0.88	3/4	5.88	15
	mm.	190.5	28.4	104.6		22.4	19.1	149.4	7
3"	in.	8.25	1.25	5	8	0.88	3/4	6.62	20
	mm.	209.6	31.8	127		22.4	19.1	168.1	9
3 1/2"	in.	9	1.38	5.5	8	1	7/8	7.25	29
	mm.	228.6	35.1	139.7		25.4	22.2	184.2	13
4"	in.	10.75	1.5	6.19	8	1	7/8	8.5	41
	mm.	273.1	38.1	157.2		25.4	22.2	215.9	19
5"	in.	13	1.75	7.31	8	1.12	1	10.5	68
	mm.	330.2	44.5	185.7		28.4	25.4	266.7	31
6"	in.	14	1.88	8.5	12	1.12	1	11.5	86
	mm.	355.6	47.8	215.9		28.4	25.4	292.1	39
8"	in.	16.5	2.19	10.62	12	1.25	1 1/8	13.75	140
	mm.	419.1	55.6	269.7		31.8	28.6	349.3	64
10"	in.	20	2.5	12.75	16	1.38	1 1/4	17	230
	mm.	508	63.5	323.9		35.1	31.8	431.8	104
12"	in.	22	2.62	15	20	1.38	1 1/4	19.25	295
	mm.	558.8	66.5	381		35.1	31.8	489	134
14"	in.	23.75	2.75	16.25	20	1.5	1 3/8	20.75	355
	mm.	603.3	69.9	412.8		38.1	34.9	527.1	161
16"	in.	27	3	18.5	20	1.62	1 1/2	23.75	495
	mm.	685.8	76.2	469.9		41.1	38.1	603.3	225
18"	in.	29.25	3.25	21	20	1.75	1 5/8	25.75	630
	mm.	743	82.6	533.4		44.5	41.3	654.1	286
20"	in.	32	3.5	23	24	1.75	1 5/8	28.5	810
	mm.	812.8	88.9	584.2		44.5	41.3	723.9	367
24"	in.	37	4	27.25	24	2	1 7/8	33	1250
	mm.	939.8	101.6	692.2		50.8	47.6	838.2	567