



BLIND FLANGE

Nominal size		Outside diam. of flange	Thick. of flange	Diam. of raised face	No. of holes	Diam. of holes	Diam. of bolts	Diam. of bolt circle	Approx. weight pounds Kg
		O	C	R					
1/2"	<i>in.</i>	4.75	0.88	1.38	4	0.88	3/4	3.25	4
	<i>mm.</i>	120.7	22.4	35.1		22.4	19.1	82.6	2
3/4"	<i>in.</i>	5.12	1	1.69	4	0.88	3/4	3.5	6
	<i>mm.</i>	130	25.4	42.9		22.4	19.1	88.9	3
1"	<i>in.</i>	5.88	1.12	2	4	1	7/8	4	8
	<i>mm.</i>	149.4	28.4	50.8		25.4	22.2	101.6	4
1 1/4"	<i>in.</i>	6.25	1.12	2.5	4	1	1	4.38	9
	<i>mm.</i>	158.8	28.4	63.5		25.4	25.4	111.3	4
1 1/2"	<i>in.</i>	7	1.25	2.88	4	1.12	1 1/8	4.88	13
	<i>mm.</i>	177.8	31.8	73.2		28.4	28.6	124	6
2"	<i>in.</i>	8.5	1.5	3.62	8	1	1	6.5	25
	<i>mm.</i>	215.9	38.1	91.9		25.4	25.4	165.1	11
2 1/2"	<i>in.</i>	9.62	1.62	4.12	8	1.12	1 1/8	7.5	35
	<i>mm.</i>	244.3	41.1	104.6		28.4	28.6	190.5	16
3"	<i>in.</i>	10.5	1.88	5	8	1.25	1 1/4	8	48
	<i>mm.</i>	266.7	47.8	127		31.8	31.8	203.2	22
4"	<i>in.</i>	12.25	2.12	6.19	8	1.38	1 1/2	9.5	73
	<i>mm.</i>	311.2	53.8	157.2		35.1	38.1	241.3	33
5"	<i>in.</i>	14.75	2.88	7.31	8	1.62	1 3/4	11.5	140
	<i>mm.</i>	374.7	73.2	185.7		41.1	44.5	292.1	64
6"	<i>in.</i>	15.5	3.25	8.5	12	1.5	2	12.5	160
	<i>mm.</i>	393.7	82.6	215.9		38.1	50.8	317.5	73
8"	<i>in.</i>	19	3.62	10.62	12	1.75	2	15.5	300
	<i>mm.</i>	482.6	91.9	269.7		44.5	50.8	393.7	136
10"	<i>in.</i>	23	4.25	12.75	12	2	2 1/2	19	510
	<i>mm.</i>	584.2	108	323.9		50.8	63.5	482.6	231
12"	<i>in.</i>	26.5	4.88	15	16	2.12	2 3/4	22.5	690
	<i>mm.</i>	673.1	124	381		53.8	69.9	571.5	313
14"	<i>in.</i>	29.5	5.25	16.25	16	2.38	2 1/4	25	975
	<i>mm.</i>	749.3	133.4	412.8		60.5	57.2	635	442
16"	<i>in.</i>	32.5	5.75	18.5	16	2.62	2 1/2	27.75	1300
	<i>mm.</i>	825.5	146.1	469.9		66.5	63.5	704.9	590
18"	<i>in.</i>	36	6.38	21	16	2.88	2 3/4	30.5	1750
	<i>mm.</i>	914.4	162.1	533.4		73.2	69.9	774.7	794
20"	<i>in.</i>	38.75	7	23	16	3.12	3	32.75	2225
	<i>mm.</i>	984.3	177.8	584.2		79.2	76.2	831.9	1009
24"	<i>in.</i>	46	8	27.25	16	3.62	3 1/2	39	3625
	<i>mm.</i>	1168.4	203.2	692.2		91.9	88.9	990.6	1644