



Nominal size		Outside diam. of flange	Thick. of flange	Diam of hub at base	Length thru hub	Diam. of bore	Fillet radius	No. of holes	Diam. of holes	Diam. of bolts	Diam. of bolt circle	Approx. weight pounds Kg
		O	C	X	Y	B	r					
1/2"	in.	<p><u>Sizes 1/2" thru 2 1/2" are identical to Class 1500</u></p>										
	mm.											
3/4"	in.											
	mm.											
1"	in.											
	mm.											
1 1/4"	in.											
	mm.											
1 1/2"	in.											
	mm.											
2"	in.											
	mm.											
2 1/2"	in.											
	mm.											
3"	in.	9.5	1.5	5	2.12	3.6	0.38	8	1	7/8	7.5	25
	mm.	241.3	38.1	127	53.8	91.4	9.7		25.4	22.2	190.5	11
4"	in.	11.5	1.75	6.25	2.75	4.6	0.44	8	1.25	1 1/8	9.25	51
	mm.	292.1	44.5	158.8	69.9	116.8	11.2		31.8	28.6	235	23
5"	in.	13.75	2	7.5	3.12	5.69	0.44	8	1.38	1 1/4	11	81
	mm.	349.3	50.8	190.5	79.2	144.5	11.2		35.1	31.8	279.4	37
6"	in.	15	2.19	9.25	3.38	6.75	0.5	12	1.25	1 1/8	12.5	105
	mm.	381	55.6	235	85.9	171.5	12.7		31.8	28.6	317.5	48
8"	in.	18.5	2.5	11.75	4.5	8.75	0.5	12	1.5	1 3/8	15.5	190
	mm.	469.9	63.5	298.5	114.3	222.3	12.7		38.1	34.9	393.7	86
10"	in.	21.5	2.75	14.5	5	10.92	0.5	16	1.5	1 3/8	18.5	275
	mm.	546.1	69.9	368.3	127	277.4	12.7		38.1	34.9	469.9	125
12"	in.	24	3.12	16.5	5.62	12.92	0.5	20	1.5	1 3/8	21	370
	mm.	609.6	79.2	419.1	142.7	328.2	12.7		38.1	34.9	533.4	168
14"	in.	25.25	3.38	17.75	6.12	14.18	0.5	20	1.62	1 1/2	22	415
	mm.	641.4	85.9	450.9	155.4	360.2	12.7		41.1	38.1	558.8	188
16"	in.	27.75	3.5	20	6.5	16.19	0.5	20	1.75	1 5/8	24.25	465
	mm.	704.9	88.9	508	165.1	411.2	12.7		44.5	41.3	616	211
18"	in.	31	4	22.25	7.5	18.2	0.5	20	2	1 7/8	27	650
	mm.	787.4	101.6	565.2	190.5	462.3	12.7		50.8	47.6	685.8	295
20"	in.	33.75	4.25	24.5	8.25	20.25	0.5	20	2.12	2	29.5	810
	mm.	857.3	108	622.3	209.6	514.4	12.7		53.8	50.8	749.3	367
24"	in.	41	5.5	29.5	10.5	24.25	0.5	20	2.62	2 1/2	35.5	1550
	mm.	1041.4	139.7	749.3	266.7	616	12.7		66.5	63.5	901.7	703