



Nominal size		Outside diam. of flange	Thick. of flange	Diam. of raised face	Diam. of hub at base	Length thru hub	Diam. of bore	No. of holes	Diam. of holes	Diam. of bolts	Diam. of bolt circle	Approx. weight pounds / Kg
		O	C	R	X	Y	B					
1/2"	in.	<p><u>Sizes 1/2" thru 3 1/2" are identical with class 600</u></p>										
	mm.											
3/4"	in.											
	mm.											
1"	in.											
	mm.											
1 1/4"	in.											
	mm.											
1 1/2"	in.											
	mm.											
2"	in.											
	mm.											
2 1/2"	in.											
	mm.											
3"	in.											
	mm.											
3 1/2"	in.											
	mm.											
4"	in.	10	1.38	6.19	5.75	2	4.57	8	1	7/8	7.88	26
	mm.	254	35.1	157.2	146.1	50.8	116.1		25.4	22.2	200.2	12
5"	in.	11	1.5	7.31	7	2.12	5.66	8	1	7/8	9.25	31
	mm.	279.4	38.1	185.7	177.8	53.8	143.8		25.4	22.2	235	14
6"	in.	12.5	1.62	8.5	8.12	2.25	6.72	12	1	7/8	10.62	44
	mm.	317.5	41.1	215.9	206.2	57.2	170.7		25.4	22.2	269.7	20
8"	in.	15	1.88	10.62	10.25	2.69	8.72	12	1.12	1	13	67
	mm.	381	47.8	269.7	260.4	68.3	221.5		28.4	25.4	330.2	30
10"	in.	17.5	2.12	12.75	12.62	2.88	10.88	16	1.25	1 1/8	15.25	91
	mm.	444.5	53.8	323.9	320.5	73.2	276.4		31.8	28.6	387.4	41
12"	in.	20.5	2.25	15	14.75	3.12	12.88	16	1.38	1 1/4	17.75	130
	mm.	520.7	57.2	381	374.7	79.2	327.2		35.1	31.8	450.9	59
14"	in.	23	2.38	16.25	16.75	3.31	14.14	20	1.38	1 1/4	20.25	180
	mm.	584.2	60.5	412.8	425.5	84.1	359.2		35.1	31.8	514.4	82
16"	in.	25.5	2.5	18.5	19	3.69	16.16	20	1.5	1 3/8	22.5	235
	mm.	647.7	63.5	469.9	482.6	93.7	410.5		38.1	34.9	571.5	107
18"	in.	28	2.62	21	21	3.88	18.18	24	1.5	1 3/8	24.75	285
	mm.	711.2	66.5	533.4	533.4	98.6	461.8		38.1	34.9	628.7	129
20"	in.	30.5	2.75	23	23.12	4	20.2	24	1.62	1 1/2	27	345
	mm.	774.7	69.9	584.2	587.2	101.6	513.1		41.1	38.1	685.8	156
24"	in.	36	3	27.25	27.62	4.5	24.25	24	1.88	1 3/4	32	510
	mm.	914.4	76.2	692.2	701.5	114.3	616		47.8	44.5	812.8	231