



THREADED FLANGE

Nominal size		Outside diam. of flange	Thick. of flange	Diam. of raised face	Diam of hub at base	Length thru hub	Min. thread length	Min. counter-bore	No. of holes	Diam. of holes	Diam. of bolts	Diam. of bolt circle	Approx. weight pounds Kg
		O	C	R	X	Y	T						
1/2"	in.	4.75	0.88	1.38	1.5	1.25	0.88	0.93	4	0.88	3/4	3.25	4
	mm.	120.7	22.4	35.1	38.1	31.8	22.4						23.6
3/4"	in.	5.12	1	1.69	1.75	1.38	1	1.14	4	0.88	3/4	3.5	5
	mm.	130	25.4	42.9	44.5	35.1	25.4						29
1"	in.	5.88	1.12	2	2.06	1.62	1.12	1.41	4	1	7/8	4	8
	mm.	149.4	28.4	50.8	52.3	41.1	28.4						35.8
1 1/4"	in.	6.25	1.12	2.5	2.5	1.62	1.19	1.75	4	1	7/8	4.38	9
	mm.	158.8	28.4	63.5	63.5	41.1	30.2						44.5
1 1/2"	in.	7	1.25	2.88	2.75	1.75	1.25	1.99	4	1.12	1	4.88	12
	mm.	177.8	31.8	73.2	69.9	44.5	31.8						50.5
2"	in.	8.5	1.5	3.62	4.12	2.25	1.5	2.5	8	1	7/8	6.5	25
	mm.	215.9	38.1	91.9	104.6	57.2	38.1						63.5
2 1/2"	in.	9.62	1.62	4.12	4.88	2.5	1.88	3	8	1.12	1	7.5	36
	mm.	244.3	41.1	104.6	124	63.5	47.8						76.2