



Nominal size		Outside diam. of flange	Thick. of flange	Diam. of raised face	Diam of hub at base	Length thru hub	Min. thread length	Min. counter-bore	No. of holes	Diam. of holes	Diam. of bolts	Diam. of bolt circle	Approx. weight pounds Kg
		O	C	R	X	Y	T						
1/2"	<i>in.</i>	5.25	1.19	1.38	1.69	1.56	1.12	0.93	4	0.88	3/4	3.5	7
	<i>mm.</i>	133.4	30.2	35.1	42.9	39.6	28.4			23.6	22.4	19.1	88.9
3/4"	<i>in.</i>	5.5	1.25	1.69	2	1.69	1.25	1.14	4	0.88	3/4	3.75	8
	<i>mm.</i>	139.7	31.8	42.9	50.8	42.9	31.8			29	22.4	19.1	95.3
1"	<i>in.</i>	6.25	1.38	2	2.25	1.88	1.38	1.41	4	1	7/8	4.25	11
	<i>mm.</i>	158.8	35.1	50.8	57.2	47.8	35.1			35.8	25.4	22.2	108
1 1/4"	<i>in.</i>	7.25	1.5	2.5	2.88	2.06	1.5	1.75	4	1.12	1	5.12	16
	<i>mm.</i>	184.2	38.1	63.5	73.2	52.3	38.1			44.5	28.4	25.4	130
1 1/2"	<i>in.</i>	8	1.75	2.88	3.12	2.38	1.75	1.99	4	1.25	1 1/8	5.75	22
	<i>mm.</i>	203.2	44.5	73.2	79.2	60.5	44.5			50.5	31.8	28.6	146.1
2"	<i>in.</i>	9.25	2	3.62	3.75	2.75	2	2.5	8	1.12	1	6.75	38
	<i>mm.</i>	235	50.8	91.9	95.3	69.9	50.8			63.5	28.4	25.4	171.5
2 1/2"	<i>in.</i>	10.5	2.25	4.12	4.5	3.12	2.25	3	8	1.25	1 1/8	7.75	55
	<i>mm.</i>	266.7	57.2	104.6	114.3	79.2	57.2			76.2	31.8	28.6	196.9