



Nominal size		Outside diam. of flange	Thick. of flange	Diam. of raised face	Diam of hub at base	Length thru hub	Min. thread length	Min. counter-bore	No. of holes	Diam. of holes	Diam. of bolts	Diam. of bolt circle	Approx. weight pounds Kg
		O	C	R	X	Y	T						
1/2"	in.	Use Class 1500 dimensions in these sizes											
	mm.												
3/4"	in.												
	mm.												
1"	in.												
	mm.												
1 1/4"	in.												
	mm.												
1 1/2"	in.												
	mm.												
2"	in.												
	mm.												
2 1/2"	in.												
	mm.												
3"	in.	9.5	1.5	5	5	2.12	1.62	3.63	8	1	7/8	7.5	26
	mm.	241.3	38.1	127	127	53.8	41.1	92.2		25.4	22.2	190.5	12
4"	in.	11.5	1.75	6.19	6.25	2.75	1.88	4.63	8	1.25	1 1/8	9.25	53
	mm.	292.1	44.5	157.2	158.8	69.9	47.8	117.6		31.8	28.6	235	24
5"	in.	13.75	2	7.31	7.5	3.12	2.12	5.69	8	1.38	1 1/4	11	83
	mm.	349.3	50.8	185.7	190.5	79.2	53.8	144.5		35.1	31.8	279.4	38
6"	in.	15	2.19	8.5	9.25	3.38	2.25	6.75	12	1.25	1 1/8	12.5	110
	mm.	381	55.6	215.9	235	85.9	57.2	171.5		31.8	28.6	317.5	50
8"	in.	18.5	2.5	10.62	11.75	4	2.5	8.75	12	1.5	1 3/8	15.5	170
	mm.	469.9	63.5	269.7	298.5	101.6	63.5	222.3		38.1	34.9	393.7	77
10"	in.	21.5	2.75	12.75	14.5	4.25	2.81	10.88	16	1.5	1 3/8	18.5	245
	mm.	546.1	69.9	323.9	368.3	108	71.4	276.4		38.1	34.9	469.9	111
12"	in.	24	3.12	15	16.5	4.62	3	12.94	20	1.5	1 3/8	21	325
	mm.	609.6	79.2	381	419.1	117.3	76.2	328.7		38.1	34.9	533.4	147
14"	in.	25.25	3.38	16.25	17.75	5.12	3.25	14.19	20	1.62	1 1/2	22	400
	mm.	641.4	85.9	412.8	450.9	130	82.6	360.4		41.1	38.1	558.8	181
16"	in.	27.75	3.5	18.5	20	5.25	3.38	16.19	20	1.75	1 5/8	24.25	425
	mm.	704.9	88.9	469.9	508	133.4	85.9	411.2		44.5	41.3	616	193
18"	in.	31	4	21	22.25	6	3.5	18.19	20	2	1 7/8	27	600
	mm.	787.4	101.6	533.4	565.2	152.4	88.9	462		50.8	47.6	685.8	272
20"	in.	33.75	4.25	23	24.5	6.25	3.62	20.19	20	2.12	2	29.5	730
	mm.	857.3	108	584.2	622.3	158.8	91.9	512.8		53.8	50.8	749.3	331
24"	in.	41	5.5	27.25	29.5	8	4	24.19	20	2.62	2 1/2	35.5	1400
	mm.	1041.4	139.7	692.2	749.3	203.2	101.6	614.4		66.5	63.5	901.7	635