



Nominal size		Outside diam. of flange	Thick. of flange	Diam. of raised face	Diam. of hub at base	Length thru hub	Diam. of bore	No. of holes	Diam. of holes	Diam. of bolts	Diam. of bolt circle	Approx. weight pounds / Kg
		O	C	R	X	Y	B					
1/2"	in.	3.5	0.44	1.38	1.19	0.62	0.88	4	0.62	1/2	2.38	1
	mm.	88.9	11.2	35.1	30.2	15.7	22.4		15.7	12.7	60.5	0.5
3/4"	in.	3.88	0.5	1.69	1.5	0.62	1.09	4	0.62	1/2	2.75	2
	mm.	98.6	12.7	42.9	38.1	15.7	27.7		15.7	12.7	69.9	1
1"	in.	4.25	0.56	2	1.94	0.69	1.36	4	0.62	1/2	3.12	2
	mm.	108	14.2	50.8	49.3	17.5	34.5		15.7	12.7	79.2	1
1 1/4"	in.	4.62	0.62	2.5	2.31	0.81	1.7	4	0.62	1/2	3.5	3
	mm.	117.3	15.7	63.5	58.7	20.6	43.2		15.7	12.7	88.9	1
1 1/2"	in.	5	0.69	2.88	2.56	0.88	1.95	4	0.62	1/2	3.88	3
	mm.	127	17.5	73.2	65	22.4	49.5		15.7	12.7	98.6	1
2"	in.	6	0.75	3.62	3.06	1	2.44	4	0.75	5/8	4.75	5
	mm.	152.4	19.1	91.9	77.7	25.4	62		19.1	15.9	120.7	2
2 1/2"	in.	7	0.88	4.12	3.56	1.12	2.94	4	0.75	5/8	5.5	7
	mm.	177.8	22.4	104.6	90.4	28.4	74.7		19.1	15.9	139.7	3
3"	in.	7.5	0.94	5	4.25	1.19	3.57	4	0.75	5/8	6	8
	mm.	190.5	23.9	127	108	30.2	90.7		19.1	15.9	152.4	4
3 1/2"	in.	8.5	0.94	5.5	4.81	1.25	4.07	8	0.75	5/8	7	11
	mm.	215.9	23.9	139.7	122.2	31.8	103.4		19.1	15.9	177.8	5
4"	in.	9	0.94	6.19	5.31	1.31	4.57	8	0.75	5/8	7.5	13
	mm.	228.6	23.9	157.2	134.9	33.3	116.1		19.1	15.9	190.5	6
5"	in.	10	0.94	7.31	6.44	1.44	5.66	8	0.88	3/4	8.5	15
	mm.	254	23.9	185.7	163.6	36.6	143.8		22.4	19.1	215.9	7
6"	in.	11	1	8.5	7.56	1.56	6.72	8	0.88	3/4	9.5	19
	mm.	279.4	25.4	215.9	192	39.6	170.7		22.4	19.1	241.3	9
8"	in.	13.5	1.12	10.62	9.69	1.75	8.72	8	0.88	3/4	11.75	30
	mm.	342.9	28.4	269.7	246.1	44.5	221.5		22.4	19.1	298.5	14
10"	in.	16	1.19	12.75	12	1.94	10.88	12	1	7/8	14.25	43
	mm.	406.4	30.2	323.9	304.8	49.3	276.4		25.4	22.2	362	20
12"	in.	19	1.25	15	14.38	2.19	12.88	12	1	7/8	17	64
	mm.	482.6	31.8	381	365.3	55.6	327.2		25.4	22.2	431.8	29
14"	in.	21	1.38	16.25	15.75	2.25	14.14	12	1.12	1	18.75	90
	mm.	533.4	35.1	412.8	400.1	57.2	359.2		28.4	25.4	476.3	41
16"	in.	23.5	1.44	18.5	18	2.5	16.16	16	1.12	1	21.25	98
	mm.	596.9	36.6	469.9	457.2	63.5	410.5		28.4	25.4	539.8	44
18"	in.	25	1.56	21	19.88	2.69	18.18	16	1.25	1 1/8	22.75	130
	mm.	635	39.6	533.4	505	68.3	461.8		31.8	28.6	577.9	59
20"	in.	27.5	1.69	23	22	2.88	20.2	20	1.25	1 1/8	25	165
	mm.	698.5	42.9	584.2	558.8	73.2	513.1		31.8	28.6	635	75
24"	in.	32	1.88	27.25	26.12	3.25	24.25	20	1.38	1 1/4	29.5	220
	mm.	812.8	47.8	692.2	663.4	82.6	616		35.1	31.8	749.3	100