



Dimensions			Thickness	Drilling Template		
NPS	OD	ID	T	# of Holes	Hole Diam.	BC
4	9.00	4.57	0.625	8	0.750	7.50
5	10.00	5.66	0.625	8	0.875	8.50
6	11.00	6.72	0.688	8	0.875	9.50
8	13.50	8.72	0.688	8	0.875	11.75
10	16.00	10.88	0.688	12	1.000	14.25
12	19.00	12.88	0.812	12	1.000	17.00
14	21.00	14.19	0.933	12	1.125	18.75
16	23.50	16.19	1.000	16	1.125	21.25
18	25.00	18.19	1.062	16	1.250	22.75
20	27.50	20.19	1.125	20	1.250	25.00
22	29.50	22.19	1.188	20	1.375	27.25
24	32.00	24.19	1.250	20	1.375	29.50
26	34.25	26.19	1.312	24	1.375	31.75
28	36.50	28.19	1.312	28	1.375	34.00
30	38.75	30.19	1.375	28	1.375	36.00
32	41.75	32.19	1.500	28	1.625	38.50
34	43.75	34.19	1.500	32	1.625	40.50
36	46.00	36.19	1.625	32	1.625	42.75
38	48.75	38.19	1.625	32	1.625	45.25
40	50.75	40.19	1.625	36	1.625	47.25
42	53.00	42.19	1.750	36	1.625	49.50
44	55.25	44.19	1.750	40	1.625	51.75
46	57.25	46.19	1.750	40	1.625	53.75
48	59.50	48.19	1.875	44	1.625	56.00
50	61.75	50.19	2.000	44	1.875	58.25
52	64.00	52.19	2.000	44	1.875	60.50
54	66.25	54.19	2.120	44	1.875	62.75
60	73.00	60.19	2.250	52	1.875	69.25
66	80.00	66.19	2.500	52	1.875	76.00
72	86.50	72.19	2.625	60	1.875	82.50
78	93.00	78.19	2.750	64	2.125	89.00
84	99.75	84.19	2.875	64	2.125	95.50
90	106.50	90.19	3.000	68	2.438	102.00
96	113.25	96.19	3.250	68	2.438	108.50
102	120.00	102.19	3.250	72	2.688	114.50
108	126.75	108.19	3.375	72	2.688	120.75
114	133.50	114.19	3.500	76	2.938	126.75
120	140.25	120.19	3.500	76	2.938	132.75
126	147.00	126.19	3.750	80	3.188	139.25
132	153.75	132.19	3.875	80	3.188	145.75
138	160.50	138.19	4.000	84	3.438	152.00
144	167.25	144.19	4.125	84	3.438	158.25

Service Rating at Atmospheric Temp - 175 PSI sizes 4-12 inches.

Service Rating at Atmospheric Temp - 150 PSI sizes 14 inches & up.

Drilling Template (DT): All sizes match ANSI B16.1, Class 125 cast iron flanges.

Drilling Template (DT): 24in. and smaller match ANSI B16.5 150# standard

All Dimension are in inches.

Other bores and facings available upon request

Furnished Flat Face unless otherwise specified