



Dimensions			Thickness	Drilling Template		
NPS	OD	ID	T	# of Holes	Hole Diam.	BC
4	9.00	4.57	1.125	8	0.750	7.50
5	10.00	5.66	1.188	8	0.875	8.50
6	11.00	6.72	1.313	8	0.875	9.50
8	13.50	8.72	1.500	8	0.875	11.75
10	16.00	10.88	1.563	12	1.000	14.25
12	19.00	12.88	1.750	12	1.000	17.00
14	21.00	14.19	1.875	12	1.125	18.75
16	23.50	16.19	2.000	16	1.125	21.25
18	25.00	18.19	2.125	16	1.250	22.75
20	27.50	20.19	2.375	20	1.250	25.00
22	29.50	22.19	2.500	20	1.375	27.25
24	32.00	24.19	2.625	20	1.375	29.50
26	34.25	26.19	2.750	24	1.375	31.75
28	36.50	28.19	2.750	28	1.375	34.00
30	38.75	30.19	2.875	28	1.375	36.00
32	41.75	32.19	3.000	28	1.625	38.50
34	43.75	34.19	3.000	32	1.625	40.50
36	46.00	36.19	3.125	32	1.625	42.75
38	48.75	38.19	3.125	32	1.625	45.25
40	50.75	40.19	3.250	36	1.625	47.25
42	53.00	42.19	3.375	36	1.625	49.50
44	55.25	44.19	3.375	40	1.625	51.75
46	57.25	46.19	3.438	40	1.625	53.75
48	59.50	48.19	3.500	44	1.625	56.00
50	61.75	50.19	3.500	44	1.875	58.25
52	64.00	52.19	3.625	44	1.875	60.50
54	66.25	54.19	3.750	44	1.875	62.75
60	73.00	60.19	3.875	52	1.875	69.25
66	80.00	66.19	4.250	52	1.875	76.00
72	86.50	72.19	4.375	60	1.875	82.50
78	93.00	78.19	4.750	64	2.125	89.00
84	99.75	84.19	4.750	64	2.125	95.50
90	106.50	90.19	5.125	68	2.438	102.00
96	113.25	96.19	5.125	68	2.438	108.50
102	120.00	102.19	5.500	72	2.688	114.50
108	126.75	108.19	5.500	72	2.688	120.75
114	133.50	114.19	5.875	76	2.938	126.75
120	140.25	120.19	5.875	76	2.938	132.75
126	147.00	126.19	6.250	80	3.188	139.25
132	153.75	132.19	6.250	80	3.188	145.75
138	160.50	138.19	6.750	84	3.438	152.00
144	167.25	144.19	6.750	84	3.438	158.25

Service Rating at Atmospheric Temp - 275 PSI

Drilling Template (DT): All sizes match ANSI B16.1, Class 125 cast iron flanges.

Drilling Template (DT): 24in. and smaller match ANSI B16.5 150# standard

All Dimension are in inches.

Other bores and facings available upon request

Furnished Flat Face unless otherwise specified