



Dimensions			Thickness	Drilling Template		
NPS	OD	ID	T	# of Holes	Hole Diam.	BC
4	10.00	4.57	1.130	8	0.875	7.88
5	11.00	5.66	1.210	8	0.875	9.25
6	12.50	6.73	1.310	12	0.875	10.62
8	15.00	8.73	1.310	12	1.000	13.00
10	17.50	10.88	1.500	16	1.125	15.25
12	20.50	12.88	1.630	16	1.250	17.75
14	23.00	14.19	1.940	20	1.250	20.25
16	25.50	16.19	2.140	20	1.375	22.50
18	28.00	18.19	2.250	24	1.375	24.75
20	30.50	20.19	2.330	24	1.375	27.00
22	33.00	22.19	2.500	24	1.375	29.25
24	36.00	24.19	2.690	24	1.625	32.00
26	38.25	26.25	3.000	28	1.875	34.50
28	40.75	28.25	3.130	28	1.875	37.00
30	43.00	30.25	3.150	28	1.875	39.25
32	45.25	32.25	3.250	28	1.875	41.50
34	47.50	34.25	3.380	28	1.875	43.50
36	50.00	36.25	3.460	32	2.125	46.00
38	52.25	38.25	3.500	32	2.125	48.00
40	54.25	40.25	3.630	36	2.125	50.25
42	57.00	42.25	3.810	36	2.125	52.75
44	59.25	44.25	4.000	36	2.125	55.00
46	61.50	46.25	4.130	40	2.125	57.25
48	65.00	48.25	4.500	40	2.125	60.75

Service Rating at Atmospheric Temp - 300 PSI

Drilling Template (DT): All sizes to match ANSI B16.1 Class 250 cast iron pipe and ASME B16.5 300# flanged fittings.

All Dimension are in inches.

Other bores and facings available upon request
Furnished Flat Face unless otherwise specified