


Straight Tees

EXTRA STRONG

Inches / Pounds



Nominal Pipe Size	Outside Diameter	Inside Diameter	Wall Thickness (T)	Center To End (C)	Center to End (M)	Pipe Schedule	Weight In Pounds
1/2	0.840	.546	.147	1.00	1.00	80	.37
3/4	1.050	.742	.154	1.12	1.12	80	.58
1	1.315	.957	.179	1.50	1.50	80	.87
1 1/4	1.660	1.278	.191	1.88	1.88	80	1.6
1 1/2	1.900	1.500	.200	2.25	2.25	80	2.3
2	2.375	1.939	.218	2.50	2.50	80	3.9
2 1/2	2.875	2.323	.276	3.00	3.00	80	6.5
3	3.500	2.900	.300	3.38	3.38	80	9.0
3 1/2	4.000	3.364	.318	3.75	3.75	80	12.2
4	4.500	3.826	.337	4.12	4.12	80	16.2
5	5.563	4.813	.375	4.88	4.88	80	26.6
6	6.625	5.761	.432	5.62	5.62	80	41.8
8	8.625	7.625	.500	7.00	7.00	80	76.2
10	10.75	9.750	.500	8.50	8.50	60	115
12	12.75	11.75	.500	10.00	10.00	*	169
14	14.00	13.00	.500	11.00	11.00	*	237
16	16.00	15.00	.500	12.00	12.00	40	284
18	18.00	17.00	.500	13.50	13.50	*	353
20	20.00	19.00	.500	15.00	15.00	30	442
24	24.00	23.00	.500	17.00	17.00	*	625
30	30.00	29.00	.500	22.00	22.00	*	1,065
36	36.00	35.00	.500	26.50	26.50	*	1,610
42	42.00	41.00	.500	30.00	28.00	*	1,788
48	48.00	47.00	.500	35.00	33.00	*	2,300

* This Size and thickness does not correspond to any pipe schedule number.

1. Dimensions conform to ASME B16.9 & material conforms to ASTM A-234 Grade B
2. For bevel detail see Weld End Bevel Detail.
3. For dimensional tolerances see Weld Fitting Dimensional Tolerances.